

# D-Poster

## Ceiling mounting




## Overview



### Round-the-clock operation

displays can be used as reliable digital signage for both offline and cloud based content 24 hours a day, 7 days a week.



### Single & Double Sided

enjoy your Advertisement single OR double sided to never miss any clients attention.



### 2000 nits

Brilliant Clarity with 2000 Nit Brightness for Showcases.



### Full HD

ensures perfect colour and rich details in all possible broadcasting surroundings, ranging from shops, to restaurants and office buildings.



### Steel Cable Suspension

This setup combines an integrated power supply within the ceiling mount and features height-adjustable, current-conducting steel cables, providing flexibility in installation and positioning.

# Specifications 43"



## Panel

<b>Panel Type:</b>	IPS / non-touch
<b>Size:</b>	43"
<b>Model No.:</b>	SAN-W4305D (Doublesided) SAN-W4305-P-D (Singlesided)
<b>Resolution:</b>	1080 x 1920
<b>Brightness:</b>	350nit (indoor), 2000nit (showcase)
<b>Contrast (Typ):</b>	1000 : 1
<b>Orientation:</b>	Portrait / Landscape
<b>Operating Hours:</b>	16 / 7
<b>Response time:</b>	8 ms
<b>Aspect ratio:</b>	16 : 9
<b>Display Area:</b>	530 x 940 mm



## Power

<b>Power Consumption:</b>	180W singlesided, 250W doublesided
<b>Power supply:</b>	Ceiling Mount with Integrated Steel Cable Suspension 500 x 85 x 80 mm



## Environment

<b>Operation Temperature:</b>	0 - 40
<b>Operation Humidity:</b>	0 - 85 %



## Operating System

<b>OS:</b>	Android
------------	---------



## Connectivity

<b>USB</b>	1 x
------------	-----



## Physical

<b>Bezel Color:</b>	Black
<b>Set Dimension (WxHxD):</b>	640 x 1110 x 42
<b>Net Weight:</b>	27,5 KG
<b>Packing Dimension (WxHxD):</b>	1290 x 750 x 165
<b>Packed Weight:</b>	39 KG
<b>Installation:</b>	Integrated Power Supply in Ceiling Mount with Adjustable, Current-Carrying Steel Cable

# Specifications 49"



## Panel

<b>Panel Type:</b>	IPS / non-touch
<b>Size:</b>	49"
<b>Model No.:</b>	SAN-W4905D (Doublesided) SAN-W4905-P-D (Singlesided)
<b>Resolution:</b>	1080 x 1920
<b>Brightness:</b>	350nit (indoor), 2000nit (showcase)
<b>Contrast (Typ):</b>	1000 : 1
<b>Orientation:</b>	Portrait / Landscape
<b>Operating Hours:</b>	16 / 7
<b>Response time:</b>	8 ms
<b>Aspect ratio:</b>	16 : 9
<b>Display Area:</b>	605 x 1075 mm



## Power

<b>Power Consumption:</b>	180W singlesided, 250W doublesided
<b>Power supply:</b>	Ceiling Mount with Integrated Steel Cable Suspension 500 x 85 x 80 mm



## Environment

<b>Operation Temperature:</b>	0 - 40
<b>Operation Humidity:</b>	0 - 85 %



## Operating System

<b>OS:</b>	Android
------------	---------



## Connectivity

<b>USB</b>	1 x
------------	-----



## Physical

<b>Bezel Color:</b>	Black
<b>Set Dimension (WxHxD):</b>	640 x 1110 x 42
<b>Net Weight:</b>	27,5 KG
<b>Packing Dimension (WxHxD):</b>	1290 x 750 x 165
<b>Packed Weight:</b>	39 KG
<b>Installation:</b>	Integrated Power Supply in Ceiling Mount with Adjustable, Current-Carrying Steel Cable

# Specifications 55"



## Panel

<b>Panel Type:</b>	IPS / non-touch
<b>Size:</b>	55"
<b>Model No.:</b>	SAN-W5505D (Doublesided) SAN-W5505-P-D (Singlesided)
<b>Resolution:</b>	1080 x 1920
<b>Brightness:</b>	350nit (indoor), 2000nit (showcase)
<b>Contrast (Typ):</b>	1000 : 1
<b>Orientation:</b>	Portrait / Landscape
<b>Operating Hours:</b>	16 / 7
<b>Response time:</b>	8 ms
<b>Aspect ratio:</b>	16 : 9
<b>Display Area:</b>	682 x 1210 mm



## Power

<b>Power Consumption:</b>	180W singlesided, 250W doublesided
<b>Power supply:</b>	Ceiling Mount with Integrated Steel Cable Suspension 500 x 85 x 80 mm



## Environment

<b>Operation Temperature:</b>	0 - 40
<b>Operation Humidity:</b>	0 - 85 %



## Operating System

<b>OS:</b>	Android
------------	---------



## Connectivity

<b>USB</b>	1 x
------------	-----



## Physical

<b>Bezel Color:</b>	Black
<b>Set Dimension (WxHxD):</b>	730 x 1260 x 50
<b>Net Weight:</b>	36,5 KG
<b>Packing Dimension (WxHxD):</b>	1430 x 830 x 175
<b>Packed Weight:</b>	38,6 KG
<b>Installation:</b>	Integrated Power Supply in Ceiling Mount with Adjustable, Current-Carrying Steel Cable